MIXTURE REQUIREMENTS

Location(s):	Hot-Mix Asphalt Surface Course						
Mixture Use(s):	Polymerized Hot-Mix Asphalt Surface Course, Mix C, N105						
AC/PG:	SBS PG76-22						
RAP % (Max):	0						
Design Air Voids:	.0%, 105 Gyration Design						
Mixture Composition: (Gradation Mixture)	IL-9.5 mm or IL12.5 mm						
Friction Aggregate:	C Surface						

Location(s):	Hot-Mix Asphalt Binder Course (Top Lift, 2 1/4")						
Mixture Use(s):	Polymerized Hot-Mix Asphalt Binder Course, N105, IL-19.0						
AC/PG:	SBS PG76-22						
RAP % (Max):	0						
Design Air Voids:	4.0%, 105 Gyration Design						
Mixture Composition: (Gradation Mixture)	IL-19.0 mm						
Friction Aggregate:	None						

Location(s):	Hot-Mix Asphalt Binder Course (Lower Lifts)				
Mixture Use(s):	Hot-Mix Asphalt Binder Course, N90, IL-19.0				
AC/PG:	PG64-22				
RAP % (Max):	10				
Design Air Voids:	4.0%, 90 Gyration Design				
Mixture Composition: (Gradation Mixture)	IL-19.0				
Friction Aggregate:	None				

Location(s):	HMA SHOULDER 12"						
Mixture Use(s):	t-Mix Asphalt Binder Course, N90, IL-19.0						
AC/PG:	PG64-22						
RAP % (Max):	10						
Design Air Voids:	0%, 90 Gyration Design						
Mixture Composition: (Gradation Mixture)	IL-19.0						
Friction Aggregate:	None						

<u> </u>					
FILE NAME =	USER NAME = \$USER\$	DESIGNED -	REVISED	-	
c:\pw_work\pwidot\lavenderba\d0290964\7	3291-sht-plan.dgn	DRAWN -	REVISED	м	ĺ
	PLOT SCALE = 100.0000 '/ in.	CHECKED ~	REVISED	*	
	PLOT DATE = 4/5/2012	DATE -	REVISED	-	

STATE	: OF	ILLINOIS
DEPARTMENT	OF	TRANSPORTATION

MIXTURE REQUIREMENTS				F.A.P RTE. 776	SECTION 125R-1	COUNTY SALINE	TOTAL SHEETS 16	SHEET NO. 4
LE: SHI	EET OF	SHEETS	STA.	TO STA.				78291